

# FASEP<sup>TM</sup>

MADE IN ITALY



## B110

PRINCIPALI FUNZIONI - Main functions - Fonctions Principales - Die Hauptsachlichen Funktionen - Principales Funciones

SETUP UTENTE - User Setup  
 Setup Client - Anwender Setup - Setup Usuario  
 CERCHI IN LEGA - Alu programs  
 Programmes Alu - Alu Programme - Aro de aleación  
 START - STOP  
 OTTIMIZZAZIONE - Tyre matching  
 Optimisation - Optimatch - Optimización  
 AUTOTARATURA - Self calibration  
 Auto étalonnage - Autokalibrierung - Autocalibración  
 AUTODIAGNOSI - Self diagnostic  
 Auto étalonnage - Selbs diagnose - Autodiagnosis

ALU-S  
 ALU-SE  
 DOPPIO OPERATORE - Twin Operator  
 Double Opérateur - Zwei Bediener System - Doble Operator  
 MOTO  
 SPLIT  
 SPLIT WEIGHT FUNCTION  
 AFC  
 AUTOMATIC FLANGE CALIBRATION  
 MARS  
 AUTOMATIC MINIMIZATION OF STATIC UMBALANCE



DOTAZIONI STANDARD / Standard equipment  
 Equipement standard / Standard ausstattungen  
 Dotación estándar



**ALU-SE**  
Sistema misura applicazione guidata dei pesi adesivi.  
Device to measure and apply adhesive weights.



Tastatore esterno  
Outside input system



Gruppo motore flangia integrato (Sistema IFS)  
Integrated bell flange (IFS system)

IMBALLO PACKING  
 EMBALLAGE VERPACKUNG  
 EMBALLAJE  
 mm. 900 x 500 x 1120 h.  
 PESO WEIGHT  
 POIDS GEWICHT  
 PESO  
 kg. 70 (lordo)  
 kg. 59 (netto)  
 DIMENSIONI  
 DIMENSIONS  
 DIMENSIONS  
 MADE  
 DIMENSIONES  
 mm. 1010 x 350 x 940 h.

CARATTERISTICHE TECNICHE - TECHNICAL DATA - CARACTERISTIQUES TECHNIQUES - TECHNISCHE DATE - CARACTERISTICAS TECNICAS

I	GB	F	D	E	
Alimentazione elettrica	Power supply	Alimentation électrique	Elektrischer Anschluß	Alimentación eléctrica	220V 50-60Hz 1Ph
Potenza assorbita	Motor rating	Puissance absorbée	Leistungsaufnahme	Potencia absorbida	60 Watt
Potenza Motore	Power Source	Poissance moteur	Motorleistung	Potencia del motor	50 Watt
Velocità di rotazione	Balancing speed	Vitesse de rotation	Auswuchtdrehzahl	Velocidad de rotación	98RPM
Diametro cerchio	Rim diameter	Diamètre jante	Felgendurchmesser	Diametro de llanta	8" (200 mm) - 26" (650 mm)
Larghezza ruota	Wheel Width	Largeur jante	Felgenbreite	Ancho rueda	max 16" (400 mm)
Peso ruota	Wheel Weight	Poids roue	Radgewicht	Peso rueda	max 90Kg (198 Lbs)
Tempo di equilibratura	Working time	Temps pour l'équilibrage	Zeit für die Auswuchtung	Tiempo de equilibrado	4 - 15 s.
Precisione	Accuracy	Précision	Ausflösung	Precisión	1 gr.



FASEP 2000 s.r.l.

Via Faentina, 96 - 50030 Ronta (Firenze) Italy - Tel. +39 055 8403126 - Fax +39 055 8403354 e-mail: info@fasep.it - www.fasep.it